

2MP 30X STARLIGHT IR PTZ HDCVI CAMERA

TB-A2323VF30

Sản xuất lắp ráp tại Nhà máy E111 - BCA

Product Image Dimensions

- Dimensions: $\Phi 205(\text{mm}) \times 336(\text{mm})$
- Weight: 8.3kg(18.30lb)
- Material: Metal
- Accessory: Adapter and junction box (included)
- Operating Conditions: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ ($-40^{\circ}\text{F} \sim +140^{\circ}\text{F}$) / Less than 90% RH



Features

- 1/2.8" 2Megapixel STARVIS™ CMOS
- Powerful 30x optical zoom
- Starlight technology
- 120dB true WDR, 3D DNR
- Max. 25/30fps@1080P, 25/30/50/60fps@720P
- IR distance up to 150m
- IP66



Accessories



Vertical Pole Mount



Corner Mount



Ceiling mount

Specifications

CAMERA	
Image Sensor	1/2.8" STARVIS™ CMOS 2 Megapixels
Illumination	0.005Lux@F1.6; 0Lux@F1.6 (IR on)
Color	
Shutter Speed	1/3s~1/30,000s
IR On/Off	Control Auto/Manual
IR LEDs	6
S/N Ratio	55 dB
IR Distance	Up to 150m (492ft)
Lens	
Focal Length	4.5mm~135mm
Max. Aperture	F1.6 ~ F5.0
Angle of View	H: 67.8° ~ 2.4°
Optical Zoom	30x
Focus Control	Auto/Manual
Close Focus Distance	100mm~ 1000mm
PTZ	
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°, auto flip 180°
Manual Control Speed	Pan: 0.1° ~160° /s; Tilt: 0.1° ~120° /s
Preset Speed	Pan: 240° /s; Tilt: 200° /s
Presets	300
PTZ Mode	5 Pattern, 8 Tour, Auto Pan ,Auto Scan
Speed Setup	Human-oriented focal Length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
Protocol	Pelco-P/D (Auto recognition)
VIDEO	
Resolution	1080P(1920×1080) / 720P(1280×720)
Frame Rate	25/30fps@1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC high definition video output/ CVBS standard definition video output (switchable)
Day/Night	Auto(ICR) / Color / B/W
OSD Menu	Support
Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto,ATW,Indoor,Outdoor,Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Digital Zoom	16x

INTERFACE	
Video Interface	1
Audio Interface	1 channel in
RS485	1
Alarm I/O	2/1
GENERAL	
Power Supply	AC24V/3A(±10%)
Power Consumption	13W,23W (IR on)



E111 FACTORY – THANH BINH BCA CO., LTD.

Industrial Zone – Lai Yen – Hoai Duc – Ha Noi

Tel: +8443-2181688 | Email : info@tbvision.com.vn | Website : tbvision.com.vn |

