

# 3MP IR FIXED BULLET NETWORK CAMERA

TB-IB2-N3711FPI-DI


## Product Image Dimensions

- Dimensions: 187.6 × 64 × 64 mm
- Weight: 0.55 kg (1.21 lb)
- Power Supply: DC12V (-15% to +25%)/PoE (IEEE 802.3af)
- Operating Conditions: -30°C to 55°C (-22°F to 131°F), Humidity less than 90% RH (non-condensing)



## Features

- 1/2.8" progressive scan CMOS
- Max. 3MP(2304×1296) @25fps resolution
- 2.8mm fixed lens (4mm optional)
- Codec H.265, H.264, MJPEG
- DWDR, 3D DNR, ROI, HLC, BLC
- Intelligent analytics: intrusion, single line crossing, double line crossing, loitering, wrong-way, and smart motion detection
- Built-in SD card slot
- Smart IR distance up to 30m
- IP67



E111 FACTORY – THANH BINH BCA CO., LTD.

Industrial Zone – Lai Yen – Hoai Duc – Ha Noi

Tel: 1800-282229 | Email : [info@tbvision.com.vn](mailto:info@tbvision.com.vn) | Website : [tbvision.com.vn](http://tbvision.com.vn) |



## Specifications

| Camera                      |   |
|-----------------------------|---|
| Image Sensor                | 1/2.8" Progressive Scan CMOS  |
| Max. Resolution             | 3MP (2304×1296)   |
| Electronic Shutter          | Auto/Manual, 1/5 to 1/20,000s   |
| Min. illumination           | Color: 0.03 Lux @ (F1.2, AGC ON), B/W: 0 Lux with IR  |
| Day & Night                 | IR cut filter   |
| Angle Adjustment            | Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°  |
| Lens                        |   |
| Lens Type                   | Fixed focus / Fixed Iris  |
| Focal Length                | 2.8mm, F2.0 (4mm optional)  |
| Field of View (FOV)         | H: 106°, V: 48°   |
| Illuminator                 |   |
| Illuminator Type            | IR  |
| Illumination Distance       | Up to 30 m (98.4 ft)  |
| Illumination On/Off Control | Auto/Manual   |
| Intelligent Analytics       |   |
| Multi-Object Detection      | Supports face, human, vehicle detection   |
| Intelligent Analysis        | Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, and Smart motion detection<br>Support alarm triggering by specified target types (human and vehicle) |
| Video                       |   |
| Streaming Capability        | Multiple streaming (3 Streams)  |
| Stream/Frame Rate           | Stream1: 2304×1296, 1920×1080, 1280×960, 1280×720 @ 25fps<br>Stream2: D1, VGA, 640×360, CIF, QVGA @ 25fps<br>Stream3: VGA, CIF, QVGA @25fps                                       |
| Bit Rate Control            | CBR/VBR   |
| Bit Rate                    | Stream1: 100 Kbps to 6 Mbps<br>Stream2: 100 Kbps to 6 Mbps<br>Stream3: 100 Kbps to 3 Mbps   |
| Region of Interest          | Off/On (8 areas, Rectangle)   |
| Smart Encode                | Support   |
| Image                       |   |
| Image Adjustment            | Brightness, Sharpness, Contrast, Saturation adjustable  |
| Scene Mode                  | Indoor, Outdoor, Mirror, Corridor mode  |
| Exposure Mode               | Auto, Manual, Shutter priority  |
| White Balance               | Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual   |
| Day/Night Setting           | Auto, Day, Night, Time  |

|                       |   |
|-----------------------|---|
| Noise Reduction       | 2D/3D DNR   |
| Image Enhancement     | HLC, BLC, DWDR  |
| Privacy Masking       | 4 areas   |
| <b>Event</b>          |   |
| Alarm Triggers        | IVS, Motion detection, Disk alarm, Network alarm  |
| Event Actions         | Alarm record, FTP upload, SMTP upload   |
| <b>Network</b>        |   |
| Protocols             | IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast |
| Interoperability      | ONVIF (Profile S/T/G/M), SDK, CGI   |
| User/Host Level       | Up to 10 users, 3 levels: Administrator, Operator, Media user   |
| Security              | IP address filter, encrypted HTTPS, Illegal login lock, IEEE 802.1x   |
| Web Viewer            | < IE11, Chrome, Firefox, Microsoft Edge   |
| Language              | English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian, Vietnamese. Default: English                           |
| <b>Interface</b>      |   |
| Network Interface     | 1 Ethernet (10/100 Base-T) RJ-45 Connector  |
| Reset Button          | Support   |
| SD Card Slot          | Built-in, up to 256TB   |
| <b>General</b>        |   |
| Power Supply          | DC12V (-15% to +25%)/PoE (IEEE 802.3af)   |
| Power Consumption     | 2W (IR OFF), Max 5.6W (IR ON)   |
| Operating Temperature | -30°C to 55°C (-22°F to 131°F )   |
| Operating Humidity    | Less than 90% RH  |
| Ingress Protection    | IP67  |
| Certifications        | CE/FCC  |
| Casing                | Aluminum alloy body   |
| Dimensions            | 187.6 × 64 × 64 mm (7.39 × 2.52 × 2.52 inch)  |
| Net Weight            | 0.55 kg (1.21 lb)   |

## Accessories



Junction Box



Pole Mount

Specifications subject to change without notice.