



3MP IR FIXED DOME NETWORK CAMERA

SECURING YOUR LIFE

TB-ID2-N3711FPI-DI

Product Image Dimensions

- Dimensions: $\phi 110 \times 85.4$ mm ($\phi 4.33 \times 3.36$ inch)
- Weight: 0.42 kg (0.93 lb)
- Power Supply: DC12V (-15% to +25%)/PoE (IEEE 802.3af)
- Operating Conditions: -30°C to 55°C (-22°F to 131°F), Humidity less than 90% RH (non-condensing)



Features

- 1/2.8" progressive scan CMOS
- Max. 3MP(2304x1296) @25fps resolution
- 2.8mm fixed lens (4mm optional)
- Codec H.265, H.264, MJPEG
- DWDR, 3D DNR, ROI, HLC, BLC
- Intelligent analytics: intrusion, single line crossing, double line crossing, loitering, wrong-way, and smart motion detection
- Built-in SD card slot
- Smart IR distance up to 30m
- IP67, IK10



E111 FACTORY – THANH BINH BCA CO., LTD.

Industrial Zone – Lai Yen – Hoai Duc – Ha Noi

Tel: 1800-282229 | Email : info@tbvision.com.vn | Website : tbvision.com.vn |



Specifications

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Max. Resolution	3MP (2304×1296)
Electronic Shutter	Auto/Manual, 1/5 to 1/20,000s
Min. illumination	Color: 0.03 Lux @ (F1.2, AGC ON), B/W: 0 Lux with IR
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 335°, Tilt: 0° to 75°, Rotation: 0° to 350°
Lens	
Lens Type	Fixed focus / Fixed Iris
Focal Length	2.8mm, F2.0 (4mm optional)
Field of View (FOV)	H: 106°, V: 48°
Illuminator	
Illuminator Type	IR
Illumination Distance	Up to 30 m (98.4 ft)
Illumination On/Off Control	Auto/Manual
Intelligent Analytics	
Multi-Object Detection	Supports face, human, vehicle detection
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way, and Smart motion detection Support alarm triggering by specified target types (human and vehicle)
Video	
Streaming Capability	Multiple streaming (3 Streams)
Stream/Frame Rate	Stream1: 2304×1296, 1920×1080, 1280×960, 1280×720 @ 25fps Stream2: D1, VGA, 640×360, CIF, QVGA @ 25fps Stream3: VGA, CIF, QVGA @ 25fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 100 Kbps to 6 Mbps Stream2: 100 Kbps to 6 Mbps Stream3: 100 Kbps to 3 Mbps
Region of Interest	Off/On (8 areas, Rectangle)
Smart Encode	Support
Image	
Image Adjustment	Brightness, Sharpness, Contrast, Saturation adjustable
Scene Mode	Indoor, Outdoor, Mirror, Corridor mode
Exposure Mode	Auto, Manual, Shutter priority

White Balance	Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual
Day/Night Setting	Auto, Day, Night, Time
Noise Reduction	2D/3D DNR
Image Enhancement	HLC, BLC, DWDR
Privacy Masking	4 areas
Event	
Alarm Triggers	IVS, Motion detection, Disk alarm, Network alarm
Event Actions	Alarm record, FTP upload, SMTP upload
Network	
Protocols	IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast
Interoperability	ONVIF (Profile S/T/G/M), SDK, CGI
User/Host Level	Up to 10 users, 3 levels: Administrator, Operator, Media user
Security	IP address filter, encrypted HTTPS, Illegal login lock, IEEE 802.1x
Web Viewer	< IE11, Chrome, Firefox, Microsoft Edge
Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian, Vietnamese. Default: English
Interface	
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Reset Button	Support
SD Card Slot	Built-in, up to 256TB
General	
Power Supply	DC12V (-15% to +25%)/PoE (IEEE 802.3af)
Power Consumption	2W (IR OFF), Max 4.5W (IR ON)
Operating Temperature	-30°C to 55°C (-22°F to 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67, IK10
Certifications	CE/FCC
Casing	Aluminum alloy body, bubble: plastic
Dimensions	φ110 × 85.4 mm (φ4.33 × 3.36 inch)
Net Weight	0.42 kg (0.93 lb)

Accessories



Junction Box



Pendant Cap



Pendant Mount



Wall Mount



Wall Mount



Pole Mount



Corner Mount

Specifications subject to change without notice.